

SINGLE USE MASK FFP2D SL WITH VALVE

Ref. 23206

TECHNICAL SHEET



MEASUREMENTS

Mask (mm)	139 x 127 x 54 (L x W x H)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Nose cushion (mm)	100 x 27 x 1.5 (L x W x T)
Valve (mm)	41 x 11 (D x H)
Superior elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inferior elastic (mm)	265 x 5 x 0.55 (L x W x T)

GENERAL DESCRIPTION AND MATERIALS

- **Singe use** protection mask **FFP2D SL with expiration valve**
- Filter media : High Filtration Efficiency Melt-Blown (polypropylene), **electrostatic**
- Synthetic rubber elastic, without latex
- Outer and inner layers in **polypropylene**
- Aluminium pince-nez
- Nose cushion in polyethylene foam
- Valve housing in polypropylene and valve membrane in synthetic rubber

SPECIFIC ADVANTAGES

- Resistance
- Comfort
- Fire proof
- Expiration valve

MAIN APPLICATION FIELDS

- Protection against dust and low toxicity solid and liquid particles up to 12xOEL
- Textile industry, craft industry, metallurgical industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls
- Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)
- **Do not use in a place where oxygen concentration is less than 17 Vol. %**

PACKAGING

- 10 masks in a bag
- **120 masks** in a box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 59765

Delivered by **BSI (notified body n° 0086)**

EN 149:2001

This mask is in conformity with the « French JO notice » 135 from 06/12/004



SACLA - Z.I. de Rosarge - 01700 LES ECHETS - MIRIBEL - FRANCE

Tél. : (33) 04 72 26 57 57 - Fax. : (33) 04 72 26 51 70 - Mail : contact@sacla-tm.fr